



TELESCOPIC BOOM WITH S.C.S. (Self Control System)

Telescopic configuration with a fixed boom and three telescopic sliding booms.

Multiple stabilization area to optimize the performance both in confined spaces and in more accessible areas. Equipped with innovative S.C.S. technology by CMC, for the optimal management of the machine. Electro-hydraulic controls and internal pipes. Top of the range.

Standard features

- Joystick on basket
- Wire portable console
- Automatic stabilization and destabilization on basket
- Back home function
- Wall function
- Memory function
- Display controls
- Truck engine on/off switch on basket
- Hour counter partial and total
- 230 V electric socket on basket
- 12V electric socket on basket
- Air-water pipe 200 Bar available on basket

FOCUS ON DETAILS



PERFORMANCE

Max. working height	24,8 m
Max. horizontal outreach	15 m
Max. basket capacity	220 Kg
Basket dimensions	1,4x0,7x1,1 m
Basket rotation	±90° (180° total)
Turret rotation	±360° (720° total)
Stabilization	Front: vertical hydraulically extractable Rear: vertical in shape
Controls	Electro-hydraulic

MINIMUM TRUCK SPECIFICATIONS

Truck GVW	3,5 t
Truck min. wheelbase	2900/3400 mm



MAX LOAD 220 KG/485 LB 120 KG/265 LB 80 KG/176 LB

